



DATASHEET:

HA-SC STANDARD CONTROLLER

HELIPORT LIGHTING CONTROLLER

Complete controller switch/distribution board for helideck lighting. It can be used as a stand-alone controller by means of the switches, remote controlled with a HA-Touch Screen or radio controlled with the HA-RRC from any aircraft. The HA-SC has a main switch and power active control lamp, 6 switches operating 6 groups with control lamps and a warning lamp in case of a malfunction.

ENCLOSURE MATERIAL	GRP
DIMENSIONS	600x600x200mm
WEIGHT	24 kg
INPUT VOLTAGE	100 – 240 VAC, (400 VAC optional)
MAX POWER	1,44 kW per group @240 VAC (or any other on request)
GROUPS	6 x RCBO, C6A, 30mA, 6kA (or any other on request)
CABLE GLAND ENTRY	1x M20 (or any other on request)
CABLE GLAND OUTLET	6x M20, 2x M16 (or any other on request)
AMBIENT TEMPERATURE	-10 °C to +55 °C
PROTECTION CAT. IP	IP66
PROTECTION CAT. NEMA	NEMA 4X
OPTIONAL	Combine with the HA-RRC (PCL-system) or HA-Touch Screen
COMPLIANCES	NEN EN 1010
HS CODE (CUSTOMS TARIFF)	94054031



Holland Aviation
Daniëlsweg 40
4451 HW Heinkenszand
The Netherlands

Tel. +31 (0)113 613467
Fax. +31 (0)113 613570
Email: info@hollandaviation.com
www.hollandaviation.com

