




DATASHEET:

HA-SC STANDARD CONTROLLER

HELIPORT LIGHTING CONTROLLER

Complete controller switch/distribution board for helideck lighting. It can be used as a stand-alone controller by means of the switches, remote controlled with a HA-Touch Screen or radio controlled with the HA-RRC from any aircraft. The HA-SC has a main switch and power active control lamp, 6 switches operating 6 groups with control lamps and a warning lamp in case of a malfunction.

ENCLOSURE MATERIAL	GRP
DIMENSIONS	640x630x230mm
WEIGHT	28 kg
INPUT VOLTAGE	380 VAC (230 VAC optional)
MAX POWER	3,5 kW per group (at 380 VAC)
GROUPS	6
CABLE ENTRY	1x M25 cable gland
CABLE OUTLET	6x M20 cable gland
AMBIENT TEMPERATURE	-40 °C to +55 °C
INGRESS PROTECTION	IP66
OPTIONAL	Combine with the HA-RCC (PCL-system) or HA-Touch Screen
COMPLIANCES	NEN EN 1010
HS CODE (CUSTOMS TARIFF)	94054031



Holland Aviation
Daniëlsweg 40
4451 HW Heinkenszand
The Netherlands

Tel. +31 (0)113 613467
Fax. +31 (0)113 613570
Email: info@hollandaviation.com
www.hollandaviation.com

