



DATASHEET:

HA-OL

OBSTRUCTION LIGHT

HA-OL is a low-intensity obstruction light to denote obstacles up to 45 meters/150 feet .

ENCLOSURE Heavy aluminium body, colour: yellow RAL 1021, chromate conversion and powder coating

DIMENSIONS Ø112x200mm

WEIGHT 1,5 Kg

LENS Borosilicate glass tempered (Red)

MOUNTING 3/4" threading in the bottom of the body

LIGHT SOURCE LED

POWER CONSUMPTION 5 watt

EXPECTED LIFETIME >75.000 hours

POWER SUPPLY 110-240VAC 50/60 Hz

LIGHT OUTPUT ICAO Class A >10 cd and ICAO Class B >32,5 cd and >50 cd (Dutch aviation authority)

AMBIENT TEMPERATURE -40 °C to + 50 °C

INGRESS PROTECTION IP 65



COMPLIANCES ICAO Annex 14 Vol. I and Vol. II heliports

UK CAP 437

UK CAP 168

EASA ADR

HS CODE (CUSTOMS TARIFF) 94054031



Holland Aviation
Daniëlsweg 40
4451 HW Heinkenszand
The Netherlands

Tel. +31 (0)113 613467
Fax. +31 (0)113 613570
Email: info@hollandaviation.com
www.hollandaviation.com

