

HA-120 RG

	The HA-120 RG is a rigid wind direction and windspeed indicator. The reliable illumination system (if present) is fixed and therefore has no rotating electric parts or slip-rings. Due to its unique design, maintenance cost and power consumption are low. The tiltable mast structure enables easy replacement of the windsock. This windsock assembly is suitable for windsocks up to Ø100cm.			
	The HA-120RG is available in a unlighted, internalighted version. The lighted windsock assemblies power supply.			
	The HA windsock sleeves have been proven to w km/h (75 knots). The windsock fabrics have been resistance and colour fastness.		•	
MAST DIAMETER	120mm			
MAST LENGHT	Standard: 4800mm (or any other lenght on request m	ax 5800m)		
MAST MATERIAL	EN-AW-6060 aluminium (brute or powder coated)			
WINDSOCK	Ø30cm up to and including Ø100cm, colour red/white orange (FAA), double stitched with reinforced front he grommets. (see other side for our standard windsock	em and		
WINDSOCK MATERIAL	Polyester, PU coated, approx. 185 gr/m ²			
WINDSOCK FRAME MATERIAL	Stainless steel AISI 316L			
SWIVEL HEAD	2 heavy duty sealed stainless steel bearings			
MAST SUPPORT AND FOUNDATION MATERIAL	Galvanised steel			
LIGHTING STYLES	Unlighted, externally lighted, internally, double lighte	d		
POWER SUPPLY	90-240VAC (50/60 HZ) or 6,6A			
POWER CONSUMPTION	Internal Lighting: 12 Watt External Lighting: 40 Watt Double lighted: 52 Watt Obstruction Light: 5 Watt			
INGRESS PROTECTION	IP65			
AMBIENT TEMPERATURE	-40°C to +60°C			
COMPLIANCES	ICAO Annex 14 Vol. I Aerodromes ICAO Annex 14 Vol. II Heliports FAA AC150/5345-27 UK CAA CAP 168 and CAP 437 EASA ADR EASA CS-HPT-DSN			ini:
HS CODE (CUSTOM TARIFF)	90158020			
	Holland Aviation Daniëlsweg 40	Tel. +31 (0)1 Fax. +31 (0)1		

© Holland Aviation. The information contained in this document is subject to modifications without prior notice.

Email: info@hollandaviation.com

www.hollandaviation.com

4451 HW Heinkenszand

The Netherlands

Holland Aviation b.v.

Airport and heliport, lighting and equipment, windsock assemblies

WINDSOCK SIZES	ØЗ

Ø300 x 1200mm	Ø700 x 2000mm
Ø300 x 1500mm	Ø700 x 2000mm reinforced leather mouth
Ø300 x 1800mm	Ø900 x 3600mm
Ø400 x 2500mm	Ø900 x 3900mm
Ø450 x 2450mm	Ø900 x 4500mm
Ø500 x 1500mm	Ø1000 x 5000mm
Ø500 x 1500mm with push button	Ø18" x 8ft (FAA size 1)
Ø600 x 2400mm	Ø36"x 12ft (FAA size 2)
Ø600 x 3000mm	Ø36"x 8ft
Ø650 x 3000mm	Or any other custom made size
	Ø300 x 1500mm Ø300 x 1800mm Ø400 x 2500mm Ø450 x 2450mm Ø500 x 1500mm Ø500 x 1500mm with push button Ø600 x 2400mm




STYLE I-A: EXTERNALLY LIGHTED




5980

STYLE I-B: INTERNALLY LIGHTED



STYLE I-AB: DOUBLE LIGHTED



Holland Aviation Daniëlsweg 40 4451 HW Heinkenszand The Netherlands Tel. +31 (0)113 613467 Fax. +31 (0)113 613570 Email: **info@hollandaviation.com** www.hollandaviation.com



© Holland Aviation. The information contained in this document is subject to modifications without prior notice.